



Eupen, 22/04/2009

**TECHNICAL SPECIFICATIONS**

	Target value	Unit	tolerance	
Foam type	<b>HDS50H/</b>			
Color	<b>brown</b>			
Width	<b>202 / 207</b>	cm	+2/+4 cm	
Height	<b>107</b>	cm	-0/+5 cm	
Density gross	<b>50,0</b>	kg/m <sup>3</sup>	+/- 5 %	
Density net	<b>47,0</b>	kg/m <sup>3</sup>	+/- 5 %	
Compression hardn.	25%	<b>120</b>	N	+/- 10 %
ISO 2439-1998	40%	<b>165</b>	N	+/- 10 %
	65%	<b>340</b>	N	+/- 12,5 %
Tensile strength ISO 1798-1997		<b>70</b>	Kpa	min.
Elongation at break ISO 1798-1997		<b>120</b>	%	min.
Compression load deflection ISO 3386-1		<b>3,90</b>	Kpa (40%)	+/- 10 %
Compression set ISO 1856-2000		<b>3,0</b>	%	max.
Fire behaviour		<b>MVSS 302 (&lt; 100 mm/min.)</b>		

Our foam types are free from CFC, HCFC and Formaldehyde.

J.-P. Doeuillet  
Qualityoffice